

TEXOL SUPER DUTY PLUS

SAE 15W40 API CF-4



JV of: **gandhar**
oil refinery (india) ltd.

Product Description

Texol® Super Duty plus SAE15W40 API CF-4 is a high performance crank case oil for diesel engines. They are formulated using high performance detergent, dispersant, wear control and anti-oxidant additives with high quality base oils. It provides excellent high temperature properties, thermal stability, low volatility and good load carrying properties.

Applications

This oil recommended for use in two and four stroke diesel engines in farm machinery, construction equipment, marine and other off-road applications. Also they are recommended for use in turbo charged and naturally aspirated two and four cycle engines

Features and Benefits

- Reduce the formation of piston deposits and varnish resulting from high temperature operation and sludge formation of low temperature service.
- Protect against wear, rust and corrosion.
- Maintains clean engine for long trouble free life.
- Reduce oil thickening due to excellent high temperature oxidation stability.

Specifications and Approvals

- API CF-4
- API CE
- API SG

Characteristics

Key Properties	Test Methods	Specification	Value
API	--	CF-4	CF-4
SAE Grade	--	15W40	15W40
Kinematic Viscosity @ 40°C	ASTM D 445	--	109.8
Kinematic Viscosity @ 100°C	ASTM D 445	12.5 to 16.3	15.2
Viscosity Index	ASTM D 2270	125 Min	145
Flash Point °C	ASTM D 92	216 Min	230
Pour Point, 0C	ASTM D 97	(-) 27 Max	(-) 30
CCS cP (-) 20°C	ASTM D5293	7,000 Max	4,900
Total Base Number	ASTM D2896	8.0 Min	10.6

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.