

# TEXOL MOTOR CYCLE OIL 4T

## SAE 20W40 API SL JASO MA-2



JV of: **gandhar**  
oil refinery (india) ltd.

### Product Description

Texol® Motor Cycle Oil 4T SAE 20W40 API SL JASO MA-2 is an high quality engine oil meeting the requirements of almost all the engines in passenger cars. It is mainly suited for turbo charged gasoline engines. As the oil also meets JASO MA-2 specification, the additives are designed for providing outstanding performance in motor cycles running on 4 stroke engines and as recommended by the OEMs.

### Applications

The oil is a semi-synthetic engine oil designed for use in modern gasoline engines. In Motor cycles, it is used in high RPM 4 stroke engines running in all terrains. While recommended for use in new technology motor bikes, the oil can also be used in earlier technology engines. Based on OEM recommendation, use is unrestricted amongst passenger cars as well as in motor cycles.

### Characteristics

Key Properties	Test Methods	Specification	Value
API	-	SL	SL
SAE Grade	-	SAE 20W40	SAE 20W40
Kinematic Viscosity @ 40°C	-	-	121
Kinematic Viscosity @ 100°C	ASTM D445	12.5 – 16.3	15.0
Viscosity Index Min	ASTM D2270	100 Min	128
CCS -15°C Max	ASTM D5293	9,500 Max	8,700
Pour Point, 0C Max	ASTM D97	(-) 15 Max	(-) 18
Base Number Min	ASTM D2896	6.0 Min	6.8
Flash Point °C Min	ASTM D92	200 Min	224

### Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.

### Features and Benefits

- As semi-synthetic engine oil, it provides excellent oxidation stability, low temperature flow properties.
- Smooth & responsive gear changes.
- Clean Engines.
- Friction characteristics provide for extra grip.
- Excellent protection from engine wear besides prolonging oil drain interval.

### Specifications and Approvals

- API-SL
- JASO MA-2