

TEXOL ULTRA MAX

SAE 5W40 API SN



JV of: **gandhar**
oil refinery (india) ltd.

Product Description

Texol® Ultra Max SAE 5W40 API SN is a fully synthetic, energy-efficient Passenger Car Motor Oil, made with high quality hydro-cracked & hydro-treated base oils and additives with proven performance. The base oils provide excellent lubricity and oxidation resistance. The engine oil provides wide temperature range operability.

Applications

Texol® Ultra Max SAE 5W40 API SN is a fully synthetic engine oil designed for use in modern gasoline engines, passenger cars, SUVs, vans and light trucks. The oil is suited for cars with direct injection (GDI) with valve timing systems and also in turbo charged gasoline engines. American and Japanese cars following API specifications oils widely use this type of engine oil.

Characteristics

Key Properties	Test Methods	Specification	Value
API	---	SN	SN
SAE Grade	---	SAE 5W40	SAE 5W40
Kinematic Viscosity @ 40°C	---	---	80.80
Kinematic Viscosity @ 100°C	ASTM D 445	12.5 – 16.3	13.30
Viscosity Index Min	ASTM D 2270	130 Min	165
CCS -30°C	ASTM D 5293	6,600 Max	6,160
Pour Point, 0C Max	ASTM D 97	(-) 33 Max	(-) 36
Base Number Min	ASTM D 2896	6.0 Min	7.3
Flash Point 0C Min	ASTM D 92	200 Min	220

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from our Texol sales office.